

HANDY TYPE NEEDLE DETECTOR

MODEL: **HN-30**

LIGHT AND EASY OPERATION

MAXIMUM SENSITIVITY
φ0.8mm



FEATURES

● **φ0.8 mm steel is detected**

This new handy type needle detector can detect φ0.8 mm steel at 5mm height from detecting unit surface.

● **Battery save function**

Under stand by, Battery mode is changed to save mode automatically and save battery consumption. When take it in hand, the machine starts automatically. New designed detecting circuit is low electric consumption.

● **Light weight**

The weight is only 190g that is more light 10% than previous model. New designed body help you to grip for long time without fatigue.

● **Large size LED lamp**

It is easy to check the detecting result by adapting large size LED lamp.

● **Sensitivity select switch**

The new handy type needle detector adopts Hi/Low sensitivity select switch.

SPECIFICATIONS

| | |
|----------------------|---|
| Model | HN-30 |
| Detecting Method | Magnetic induction |
| Detecting ability | Hi : φ0.8mm steel at 5mm height from detecting surface. Low : φ1.0mm steel at 5mm height from detecting surface. |
| Detecting adjustment | 2 step |
| Detecting area | 25mm(W) x 50mm(D) |
| Alarm method | Buzzer, LED lamp |
| Power supply | 1.5V dry cell battery X2 (AAA) |
| Dimension | 58 (W) X 195 (L) X 50 (H) mm |
| Weight | 212g |

Detected material should be used UNTIL METAL ITEM.

※The specification is under standard test condition. The sensitivity depends on the working condition.

We have no responsibility that needle chip, iron chip, etc. come out after detecting under non-standard condition.