

- The data is directly transferred to computer via USB cable, the docking station is not required.
- Water Resistant IP 65.
- Hi-Low set-up alarm.
- USB interface for set-up and data download.
- Fast USB download speed-download 50K records in less than 10 seconds.

TM-305U Water Proof IP 65



patent pending

USB Temperature Humidity Datalogger

- Humidity Sensor Type : Capacitive.
- Sensor Type : NTC.
- Channel(s) : 2.
- Range : -40°C to +85.0°C / -40°F to +185.0°F
- Accuracy : 0.6°C (1.2°F) from -20~50°C (-4 to 122°F)
1.0°C (1.8°F) all other rangers.
- Range : 1-99% RH.
- Accuracy : ±3.0% RH (20~80%RH) ±5.0% (<20% ,>80%RH)
- Interface : USB.
- Datalogger Memory : 50,000 records.
- Dimension : 83X 60 X24mm.

TM-306U Water Proof IP 65



patent pending

USB Temperature Datalogger

- Sensor Type : NTC.
- Channel (s) : 1.
- Range : -40°C to 85°C. (-40°F to 185.0°F)
- Accuracy :
0.6°C (1.2°F) from -20 to 50°C. (-4 to 122°F)
1.0°C (1.8°F) all other rangers.
- Interface : USB.
- Datalogger Memory : 50,000 records.
- Dimension : 83X60X24mm.